



REV	ZONE	REVISION	DATE

**Green Product**

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	BRASS T:0.4	NICKEL PLATED	1
2	SPRING TERMINAL	PHOS. BRONZE T:0.30	TIN PLATED	1
3	TERMINAL	BRASS T:0.4	TIN PLATED	1
4	HOUSING	PBT G.F.	W.Y.R.B.L.N.D	1

**Order Information**  
**8710-1B3xE**

Housing Color  
W: WHITE  
Y: YELLOW  
R: RED  
Special :  
B: BLACK  
L: BLUE  
O: ORANGE  
N: GREEN

Specification:  
Contact Resistance: 30m Ohm Max. At AC 100mA Max.1KHz.  
Insulation Resistance: 100M Ohm Min. At 500V DC.  
Rated Voltage And Current: DC 12V,2A Max.  
Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.  
Durability (Life Test): 4000 Cycles.  
Insertion Force: 0.3~3.0 Kg.  
Extraction Force: 0.3~3.0 Kg.

**LEAMAX** 易昕企業有限公司  
LEAMAX ENTERPRISE CO., LED.

Drawing No			UNIT	SCALE	TITLE	
8710-1S2			mm	1:1	RCA JACK	
APPD.	CKD.	DWG.	DATE	TOLERANCE	PART NO.	REV.
JAMES 04-09-17	SHIRLEY 01-09-17	TINA 25-12-07	25-12-07	X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05	8710-1B3x-3SE	A0

MODEL 8710-1B3x-3SE PAGE 1 OF 1