

Features:

- Available in 2 thru 24 circuits
- Material: UL 94V-0 Nylon
- Accepts 4312-FT Terminal
- Mates with 4312-2xxHFE Housing
- Standard color: Black

Specifications:

- Current rating:

Wire size	# 20	# 22	# 24	# 26	# 28	# 30
Ampere	5 A	5 A	4 A	3 A	2 A	1 A

- Voltage rating: 250V AC(RMS) or DC
- Insulation resistance: 1000M Ω Min.
- Dielectric strength: 1500V AC/minute
- Temperature rise: 30°C Max.
(carry rated current load)

Dimensional Information

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2		4.0	6	6.0	10.0	10	12.0	16.0	14	18.0	22.0	18	24.0	28.0	22	30.0	34.0
4	3.0	7.0	8	9.0	13.0	12	15.0	19.0	16	21.0	25.0	20	27.0	31.0	24	33.0	37.0

Order Information

P N : 4 3 1 2 - 2 x x H M E

Serial Type _____ E: RoHS
 No. of Contact _____
 02~24 PIN
 H: Housing
 M: Male

TOLERANCE	APPROVALS	DATE	易昕企業有限公司 LEAMAX ENTERPRISE CO., LTD.		
.000 $\pm$ 0.08 (mm)	DRAWN Daniel	29-07-00	TITLE: .118" (3.00mm) Dual Row Receptacle Housing DWG NO.4312-HMB		
.00 $\pm$ 0.25 (mm)	CHK'D Huang	01-04-15			
.0 $\pm$ 0.4 (mm)	APP'D Chen	07-05-15			
UNTS mm		SCALE 1:1	SIZE A4	SHEET 1 OF 1	REV. C/D

REV	ECN NO.	DESCRIPTION	DATE	APP'D
C/D		RELEASE TO PRODUCTION		Paul

